

High Speed Compact Automatic Strapping Machine

The SQ-800IR3 boasts all of the advanced features of the SQ-800 such as self-loading, refeed and loop ejection, in an attractive and compact body.

- **Compact and Hand-Free**
Space-efficient design with internal reel unit utilizing a standard size strap coil. This compact body is ideal for printing and mailing applications. The integrated foot arm switch under the body provides hands-free operation.
- **High Speed**
Standard trapping rate is 60 straps/min, even when a tension is applied. The machine is ready to operate in less than 25 seconds, contributing to increased packaging line efficiencies.
- **Less Dusting and Less Moving Parts, with Self-Lubricating Design**
The upgraded sealing head utilizing DC motors means less moving parts and less dusting from plastic strapping. It also reduces the maintenance cost. Strapack's signature self-lubricating design also reduces wear and tear, allows for easier maintenance, and increases operational life of the machine.
- **Arch Configuration**
Arch configuration accommodates U.S. Mail trays with 690mm (27") opening.



SQ-800IR3

Standard Specifications (Arch size 690 mm wide x 400 mm high or 27" wide x 16" high)

Dimension	Width	1052 mm (with handles)	41-3/8 in. (with handles)
	Height	1445 mm	56-7/8 in.
	Depth	609 mm	24 in.
	Weight	161 kg	355 lbs.
Table Height		936 mm	36-7/8 in.
Package Size	Max	W 620 X H380 mm	W 24-1/2 X H 15 in.
	Min	W 80 X H 30 mm	W 3-1/8 X H 1-1/8 in.
Joint / Strap		heat seal / polypropylene	heat seal / polypropylene
Strap		5, 6, 9, 12, 15.5 mm	1/4, 3/8, 1/2 in.
Strap Tension		784 N (80 kgf)	176 lbf
Power Supply		100, 120, 220, 230, 240V Single phase 50/60Hz 0.74kVA	

Dimensions and specifications are subject to change without notice.

Modification rights reserved.

© 2019 Strapack Corporation

DISTRIBUTED BY:



ISO 9001 and 14001 Certified

STRAPACK CORPORATION
8-16-6 Ginza, Chuo-ku, Tokyo, 104-0061, JAPAN
Phone 81-3-6278-1806 Fax. 81-3-6278-1807
(URL) <http://www.strapack.com> (E-mail) info@strapack.com
STRAPACK INC.
33508 Central Avenue, Union City, CA 94587-2097 U.S.A.
Phone 1-510-475-6000 Fax. 1-510-475-6090
STRAPACK, N.V./S.A.
Uilenbaan 200, B-2160 Wommelgem, BELGIUM
Phone 32-(0)3-355-1520 Fax. 32-(0)3-355-1521